

**ZHEJIANG YONGHE REFRIGERANT
CO., LTD.
QUZHOU, ZHEJIANG, CHINA 324022
Tel.: 86-570-8886807, 3832776 Fax: 86-570-3832767**

Material Safety Data Sheet (REFRIGERANT 410A)

Information in this format is provided as a service to our customers and is intended only for their use. Others may use it at their own discretion and risk. This information is based upon technical information. It is subject to revision as additional knowledge and experience are gained. Please return to this website for the most current version.

R 410A

2187FR

Revised 23-MAR-2004

IDENTIFICATION OF THE SUBSTANCE

PRODUCT NAME: R410A

COMPOSITION/INFORMATION ON INGREDIENTS

EC No.: 200-839-4 HFC 32, 206-557-8 HFC 125				
HAZARDOUS INGREDIENT(S)	CAS No.	%(w/w)	Symbol	R Phrases
Difluoromethane(HFC 32)	75-10-5	50	F+	R1
Pentafluoroethane(HFC 125)	354-33-6	50		

HAZARDS IDENTIFICATION

Low acute toxicity. High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anesthetic effects and asphyxiation.
Liquid splashes or spray may cause freeze burns to skin and eyes.

FIRST AID MEASURES

The first aid advice given for skin contact, eye contact, and ingestion is applicable following exposures to the liquid or spray. See also section 11.

INHALATION

Remove patient from exposure, keep warm and at rest. Administer oxygen if necessary. Apply artificial respiration if breathing has ceased or shows signs of failing. In the event of cardiac arrest apply external cardiac massage. Obtain immediate medical attention.

SKIN CONTACT

Thaw affected areas with water. Remove contaminated clothing. Caution: clothing may adhere to the skin in the case of freeze burns. After contact with skin, wash immediately with plenty of warm water. If irritation or blistering occurs obtain medical attention.

EYE CONTACT

Immediately irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 10 Minutes. Obtain immediate medical attention.

INGESTION

Do not induce vomiting. Provide the patient is conscious, wash out mouth with water and give 200-300 ml(half a pint) of water to drink. Obtain immediate medical attention.

Further Medical Treatment

Symptomatic treatment and supportive therapy as indicated.

Adrenaline and similar sympathomimetic drugs should be avoided following exposure as cardiac arrhythmia may result with possible subsequent cardiac arrest.

FIRE FIGHTING MEASURES

The refrigerant is not flammable in air under ambient of temperature and pressure. Certain mixtures of this refrigerant and air when under pressure may be flammable. Mixtures of this refrigerant and air under pressure should be avoided. Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions.

Thermal decomposition will evolve very toxic and corrosive vapors. (hydrogen fluoride)

Containers may burst if overheated.

Extinguish Media: As appropriate for surrounding fire. Water spray should be used to cool containers.

Fire Fighting Protective Equipment: A self contained breathing apparatus and suitable protective clothing must be worn in fire conditions. See Section 8.

ACCIDENTAL RELEASE MEASURES

Ensure suitable personal protection (including respiratory protection) during removal of spillages. See Section 8.

Provided it is safe to do so, isolate the source of the leak. Allow small spillages to evaporate provided there is adequate ventilation.

Large spillages: Ventilate area. Contain spillages with sand, earth or any suitable adsorbent material. Prevent liquid from entering drains, sewers, basement and work pits since the vapor may create a suffocating atmosphere.

HANDLING AND STORAGE

HANDLING

Avoid inhalation of high concentrations of vapours. Atmospheric level should be controlled in compliance with the occupational exposure limit. Atmosphere concentrations well below the occupational exposure limit can be achieved by good occupational hygiene practice .

The vapour is heavier than air , high concentrations may be produced at low levels where general ventilation is poor, in such cases provide adequate ventilation or wear suitable respiratory protective equipment with positive air supply.

Avoid contact with naked flames and hot surfaces as corrosive and very toxic decomposition products can be formed.

Avoid contact between the liquid and skin and eyes.

For correct refrigerant composition, systems should be changed using the liquid phase and not the vapour phase.

Process Hazards

Liquid refrigerant transfers between refrigerant containers and to and from systems can result in static generation. Ensure adequate earthing. Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions.

STORAGE

Keep in a cool place away from fire risk , direct sunlight and all sources of heat such as electric and steam radiators. Avoid storing near to the intake of air conditioning units, boiler units and open drains.

Cylinders and Drums:

Keep container dry.

Storage temperature(Deg C): < 45

EXPOSURE CONTROLS/PERSONAL PROTECTION

Wear suitable protective clothing , gloves and eye /face protection. Wear thermal insulating gloves when handling liquefied gases. In cases of insufficient ventilation, where exposure to high concentrations of vapour is possible, suitable respiratory protective equipment with positive air supply should be used.

Occupational Exposure Limits

HAZARDOUS	LIEL 8hr	LIEL 8hr	STEL	STEL	Notes
Pentafluoroethane(HFC125) COM	1000		-	-	-
Difluoromethane (HFC 32) COM	1000		-	-	-

PHYSICAL AND CHEMICAL PROPERTIES

Form:	liquefied gas
Colour:	colourless
Odour:	slight ethereal
Boiling Point (Deg C):	-51.58 to -51.9(boiling range)
Vaper Pressure (mm Hg):	10880 at 20 Deg C
Density (g/ml):	1.09 at 20 Deg C
Solubility (Water):	insoluble
Solubility (Other):	soluble in chlorinated solvents, alcohols, esters
Vapour Density	2.6 at bubble point temperature

STABILITY AND REACTIVITY

Hazardous Reactions

Certain mixtures of HFCs and chlorine may be flammable or reactive under certain conditions.

Incompatible materials: finely divided metal, magnesium and alloys containing more than 2% magnesium.

Can react violently if in contact with alkali metals and alkaline earth metals-sodium, potassium, barium.

Hazardous Decomposition Product(s):hydrogen fluoride by thermal decomposition and hydrolysis

TOXICOLOGICAL INFORMATION

In halation

High exposure may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anesthetic effects and asphyxiation.

Skin Contact

Liquid splashes or spray may cause freeze burns. Unlike to be hazardous by skin absorption.

Eye Contact

Liquid splashes or spray may cause freeze burns.

Ingestion

Highly unlikely - but should this occur freeze burns will result.

Long Term Exposure

HFC32: An inhalation study in animals has shown that repeated exposures produce no significant

Effects -49500ppm in rats

HFC 125: An inhalation study in animals has shown that repeated exposures produce significant

Effects -50000ppm in rats

ECOLOGICAL INFORMATION

Environmental Fate and Distribution

High tonnage material produced in wholly contained systems. High tonnage material used

In open systems. Vapour

Persistence and Degradation

HFC32: Decomposed comparatively rapidly in the lower atmosphere(troposphere) .

Atmospheric lifetime is 5.6 year(s)

Has a Global Warming Potential (GWP) of 650(relative to a value of 1 for carbon dioxide at 100 year (s)

HFC 125: Decomposed slowly in the lower atmosphere (proposphere) . atmospheric lifetime is 32.6 year(s)

Has a Global Warming Potential (GWP) of 2800(relative to a value of 1 for carbon dioxide at 100 year (s)

HFC32 , HFC 125: Does not influence photochemical smog(i.e. is not a Voc under the terms of the UNECE agreement). Does not deplete ozone

Effect on Effluent Treatment

Discharges of the product will enter the atmosphere and will not result in long term aqueous contamination.

DISPOSAL CONSIDERATIONS

Best to recover and recycle. If this is not possible, destruction is to be in at approved facility which is equipped to absorb and neutralize acid gases and other toxic processing products.

TRANSPORTATION INFORMATION

UN No.:	3163
AIR	
ICAO/LATA	
-primary:	2.2
SEA	
IMDG	
- primary:	2.2
Marine Pollutant:	Not classified as a Marine Pollutant
Proper Shipping Name:	REFRIGERANT GAS, N.O.S. (DIFLUOROMETHANE, PENTAFLUOROETHANE)
ROAD/RAIL	
ADR/RID Class:	2
ADR Sin:	3163

REGULATORY INFORMATION

Nor Classified as Hazardous to Users.

OTHER INFORMATION

The following sections contain revisions or new statements: 1.12.14.16
Information in this publication is believed to be accurate and is given in good faith, but is for the Customer to satisfy itself of the suitability or its own particular purpose.
End of MSDS



ZHEJIANG YONGHE REFRIGERANT CO.,LTD.

Product: MIXED REFRIGERANT GAS R410A Batch No.: 1-2102211

Standard: Q/ZYH013-2019 The date of production: FEB 21ST, 2021

Items	Unit	Index	Inspection Results
Appearance		Colorless and no turbid	Qualified
Odor		No strange stench	Qualified
Purity	% (>)	99.90	99.95
Moisture	% (≤)	0.0010	0.0008
Acidity	(as HCL) %	≤0.0001	≤0.0001
Vapor Residue	% (≤)	0.01	≤0.01
Conclusion	QUALIFIED		
Remark	XXB032/YH2102		

Inspector: Du Heng

Review: Ke Xuemei

Check: Chen Yi

浙江永和制冷股份有限公司
ZHEJIANG YONGHE REFRIGERANT CO.,LTD.